

## PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

## FEATURES:

- Double ended Type A
- Single ended Type B
- Shatterproof glass
- Input voltage is AC110V-277V
- Low thermal decay
- Low maintenance
- No mercury, lead-free
- No UV

## COMPATIBLE BALLAST LIST:

- [For compatible ballasts, please check on the website under the Tube section > Plug & Play LED Glass Shatterproof > Ballast List](#)

## Shatterproof Proof Plug & Play Tube 4FT 17W Spec

LOD-GDMT84F-17W40KF

LOD-GDMT84F-17W50KF



## SPECIFICATIONS:

| SPECIFICATION         | Details                             |                                     |
|-----------------------|-------------------------------------|-------------------------------------|
| Model                 | LOD-GDMT84F-17W40KF                 | LOD-GDMT84F-17W50KF                 |
| Input Wattage (W)     | 17W                                 | 17W                                 |
| Lumens Delivered (LM) | 2,300LM                             | 2,300LM                             |
| Efficacy (LM/W)       | 136LM/W                             | 136LM/W                             |
| CRI                   | 80                                  | 80                                  |
| Lifespan              | 50,000 hours                        | 50,000 hours                        |
| Color Temperature     | 4,000K                              | 5,000K                              |
| Wattage Equivalent    | 32W – 36W                           | 32W – 36W                           |
| Dimmable              | No                                  | No                                  |
| IP Rating             | IP40                                | IP40                                |
| Beam Angle            | 270                                 | 270                                 |
| Input Voltage         | AC110-277V                          | AC110-277V                          |
| Power Factor          | 0.9                                 | 0.9                                 |
| Housing               | Glass                               | Glass                               |
| Lens                  | Frosted                             | Frosted                             |
| Mounting              | G13                                 | G13                                 |
| Size                  | 48"                                 | 48"                                 |
| Weight (LBS)          | 10%                                 | 10%                                 |
| Certification         | DLC, UL, FCC, CE RoHS, TUV, ISO9001 | DLC, UL, FCC, CE RoHS, TUV, ISO9001 |
| Operating Temperature | -20°C to 50°C (-4°F to 122°F)       | -20°C to 50°C (-4°F to 122°F)       |
| Environment           | Indoor                              | Indoor                              |
| Warranty              | 5 years limited                     | 5 years limited                     |

