

## PRODUCT DESCRIPTION:

T8 linear tube retrofits provide exceptional lighting for areas such as, commercial buildings, hotels, conference rooms, schools and office buildings.

## FEATURES:

- Input voltage is AC110V-277V
- Low maintenance
- Environmentally friendly
- No mercury
- Recyclable

## Integrated Tube 18W Spec

LOD-T8B-1200NF(40K120C120)

LOD-T8B-1200NF(50K120C120)



## SPECIFICATIONS:

SPECIFICATION	Details	Details
Model	LOD-T8B-1200NF(40K120C120)	LOD-T8B-1200NF(50K120C120)
Input Wattage (W)	18W	18W
Lumens Delivered (LM)	2,198.2LM	2,456.1LM
Efficacy (LM/W)	113.19LM/W	126.54LM/W
CRI	82.3	81.4
Lifespan	50,000 hours	50,000 hours
Color Temperature	4,000K	5,000K
Wattage Equivalent	36W	36W
Dimmable	No	No
IP Rating	IP40	IP40
Beam Angle	120	120
Input Voltage	AC110-277V	AC110-277V
Power Factor	0.9063	0.9152
Housing	Aluminum	Aluminum
Lens	Frosted	Frosted
THD	18.25%	17.96%
Mounting	T8 Integrated Cap	T8 Integrated Cap
Size	48"	48"
Certification	DLC, UL, FCC, CE RoHS, TUV, ISO9001	DLC, UL, FCC, CE RoHS, TUV, ISO9001
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	-20°C to 50°C (-4°F to 122°F)
Environment	Indoor	Indoor
Warranty	5 years limited	5 years limited

