

PRODUCT DESCRIPTION:

T5 can be used in commercial buildings such as, hotels, conference rooms, schools and office buildings.

FEATURES:

- Double ended Type A
- Input voltage is AC110V-277V
- Low thermal decay
- No mercury
- Recyclable
- Low maintenance

T5 Tube 24W Spec

LOD-T54FT-24W40K

LOD-T54FT-24W50K



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-T54FT-24W40K	LOD-T54FT-24W50K
Input Wattage (W)	24W	
Lumens Delivered (LM)	2,900LM	3,000LM
Efficacy (LM/W)	121LM/W	125LM/W
CRI	82	82
Lifespan	50,000 hours	
Color Temperature	4,000K	5,000K
Wattage Equivalent	54W	
Dimmable	No	
IP Rating	IP20	
Beam Angle	270	
Input Voltage	AC110-277V	
Power Factor	0.9	0.9
Housing	Plastic	
Lens	Frosted	
Mounting	G5	
Size	4FT	
THD	8.2%	8.2%
Certification	UL, FCC, CE RoHS, TUV, ISO9001	
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	
Environment	Indoor	
Warranty	5 years limited	

