

LEDone

Projects:

Comments:

8 inch 40w commercial downlight retrofit

SPECIFICATIONS:

WATTAGE:	40W
MODEL #:	DLRC0840HU40K10D
CERTIFICATIONS:	UL, FCC, CE
VOLTAGE:	120-277
POWER FACTOR:	0.9 min
FREQUENCY:	50/60Hz
LUMENS EFFICIENCY:	75 LPW
KELVIN (CCT):	4000K
THD:	20% max.
CRI:	80 min.
MATERIALS:	Aluminum
LED CHIPS:	Cree
LIFE SPAN (HOURS):	50,000 hours
DIMMING COMPATIBLE:	0-10V
LENGTH OF WARRANTY (YEARS):	5 years
PRODUCT HEIGHT:	9.29"
PRODUCT DIAMETER:	8.89"
WORKING ENVIRONMENT:	Indoor
SUGGESTED REPLACEMENT FOR:	2x26W PL
POWER EFFICIENCY:	0.85 typ.
PERCENTAGE OF WATTAGE SAVED:	25%



Features:

Supplied with a heavy gauge anodized aluminum reflector

Integral cast aluminum heat sink conducts heat away from LED light engine

Driver is accessible from below the ceiling and can be upgraded to accommodate future technology improvements

Applications:

Classroom, conference room, lobby/reception, open offices, retail, corridor, private office

