

PRODUCT DESCRIPTION:

Designed to fit any ceiling surface. Suspended and hanging for other types of ceilings such as art galleries, homes, schools, offices, hotels, restaurants, retail stores and other commercial or industrial applications.

FEATURES:

- Triac Dim
- Low maintenance
- Environmentally friendly
- No mercury
- Recyclable
- Junction Box

DIMENSIONS:

6" Downlight 15W Spec

LOD-DL6RF-D15W40K

LOD-DL6RF-D15W50K



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-DL6RF-D15W-40K	LOD-DL6RF-D15W-50K
Input Wattage (W)	15W	15W
Lumens Delivered (LM)	1,110.70LM	1,130.30LM
Efficacy (LM/W)	79.96LM/W	80.39LM/W
CRI	93.8	93.2
Lifespan	25,000 hours	25,000 hours
Color Temperature	4,000K	5,000K
Wattage Equivalent	60W	60W
Dimmable	Triac Dim	Triac Dim
IP Rating	Damp Location	Damp Location
Beam Angle	95	95
Input Voltage	110-277VAC	110-277VAC
Power Factor	0.987	0.988
Housing	Aluminum	Aluminum
Lens	Frosted	Frosted
Mounting	Junction Box	Junction Box
Size		
Certification	ES, ETL, FCC, CE RoHS, TUV, ISO9001	ES, ETL, FCC, CE RoHS, TUV, ISO9001
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	-20°C to 50°C (-4°F to 122°F)
Environment	Indoor	Indoor
Warranty	3 years limited	3 years limited

